



WATER FILTER HOUSINGS

SpiroPure filter housings come in single, twin, and triple housing combinations. Each housing option comes with a filter housing wrench and mounting bracket. Can be used with sediment, carbon, descaler, and more filter cartridges. Explore our housing options with and without pressure relief buttons.

- Durable housings that come in single, twin, and triple housing options
- 4.5" BB models offer a double O-ring for a better seal to prevent unwanted leaks
- Available in nominal sizes of: 10x2.5, 10x4.5, 20x2.5, and 20x4.5
- Each housing option includes a filter housing wrench and metal mounting bracket
- SpiroPure filter housings are composed of premium polypropylene for quality filtration

FILTER DETAILS CHART

Model Number	Number of Housings	Size	Inlet/Outlet	Color	Pressure Relief Button	Temperature Rating	Pressure Drop	Case Quantity
SP-FH-BL14	Single	10" x 2.5"	1/4" NPT	Blue	No	40°F - 125°F (4.4°C - 51.7°C)	90 psi (6.20 bar)	12
SP-FH-CL14	Single	10" x 2.5"	1/4" NPT	Clear	No	40°F - 125°F (4.4°C - 51.7°C)	90 psi (6.20 bar)	12
SP-FH-BL12	Single	10" x 2.5"	1/2" NPT	Blue	No	40°F - 125°F (4.4°C - 51.7°C)	90 psi (6.20 bar)	12
SP-FH-BL12PR	Single	10" x 2.5"	1/2" NPT	Blue	Yes	40°F - 125°F (4.4°C - 51.7°C)	90 psi (6.20 bar)	12
SP-FH-BL34PR-BB	Single	10" x 4.5"	3/4" NPT	Blue	Yes	40°F - 100°F (4.4°C - 37.8°C)	90 psi (6.20 bar)	4
SP-FH-BL10PR-BB	Single	10" x 4.5"	1" NPT	Blue	Yes	40°F - 100°F (4.4°C - 37.8°C)	90 psi (6.20 bar)	4
SP-FH-TWIN10PR-BB	Twin	10" x 4.5"	1" NPT	Blue	Yes	40°F - 100°F (4.4°C - 37.8°C)	90 psi (6.20 bar)	1
SP-FH-TRIPLE10PR-BB	Triple	10" x 4.5"	1" NPT	Blue	Yes	40°F - 100°F (4.4°C - 37.8°C)	90 psi (6.20 bar)	1
SP-FH-BL12-20	Single	20" x 2.5"	1/2" NPT	Blue	No	40°F - 125°F (4.4°C - 51.7°C)	90 psi (6.20 bar)	6
SP-FH-BL12PR-20	Single	20" x 2.5"	1/2" NPT	Blue	Yes	40°F - 125°F (4.4°C - 51.7°C)	90 psi (6.20 bar)	6

Model Number	Number of Housings	Size	Inlet/Outlet	Color	Pressure Relief Button	Temperature Rating	Pressure Drop	Case Quantity
SP-FH-BL34PR-20BB	Single	20" x 4.5"	3/4" NPT	Blue	Yes	40°F - 100°F (4.4°C - 37.8°C)	90 psi (6.20 bar)	4
SP-FH-BL10PR-20BB	Single	20" x 4.5"	1" NPT	Blue	Yes	40°F - 100°F (4.4°C - 37.8°C)	90 psi (6.20 bar)	4
SP-FH-TWIN10PR-20BB	Twin	20" x 4.5"	1" NPT	Blue	Yes	40°F - 100°F (4.4°C - 37.8°C)	90 psi (6.20 bar)	1
SP-FH-TRIPLE10PR-20BB	Triple	20" x 4.5"	1" NPT	Blue	Yes	40°F - 100°F (4.4°C - 37.8°C)	90 psi (6.20 bar)	1

ACCESSORIES

Model Number	Product Name	Description			
SP-FH-MB-SINGLE	Single Housing Metal Mounting Bracket	Designed for mounting a single water filter housing			
SP-FH-MB-TWIN	Twin Housing Metal Mounting Bracket	Designed for mounting a twin water filter housing.			
SP-FH-MB-TRIPLE	Triple Housing Metal Mounting Bracket	Designed for mounting a triple water filter housing.			
SP-FH-WRENCH	Slim Filter Housing Wrench	Designed for use with standard slim 2.5" water filter housings.			
SP-FH-WRENCH-BB	BB Filter Housing Wrench	Designed for use with standard BB 4.5" water filter housings.			
SP-FH-ORING	O-ring for Slim Housings	Designed for slim 2.5" water filter housings.			
SP-FH-ORING-BB-U	O-ring for BB Housings (Upper)	Designed for BB 4.5" water filter housings.			
SP-FH-ORING-BB-L	O-ring for BB Housings (Lower)	Designed for BB 4.5" water filter housings.			

